OPEN TOP OFFSHORE CONTAINER





Product Features:

- Certification: DNV 2.7-1 / EN 12079
- Optional slings: DNV 2.7-1 certified
- Design temperature to -40°C
- Multiple internal tie-down points
- Built-in lifting pad eyes and ISO corner castings for easy transport
- Standard forklift pockets
- Tarpaulins complete with roof bars
- Internal lashing points for securing cargo, each lashing bar or ring capable to withstand a force of 1,000kg
- Ideal for overheight cargo



















| Item | | 10'x8'x8'6" | 20′x8′x4′ |
|-----------------------|-------------|-------------|-----------|
| External | Length (mm) | 2,991 | 6,058 |
| Dimension | Width(mm) | 2,438 | 2,438 |
| | Height(mm) | 2,591 | 2,591 |
| Internal Dimension | Length (mm) | 2,818 | 5,848 |
| | Width(mm) | 2,318 | 2,300 |
| | Height(mm) | 2,124 | 2,225 |
| Gross Weight (kg) | | 10,000 | 20,000 |
| Tare Weight (kg) | | 2,250 | 4,000 |
| Max Payload (kg) | | 7,750 | 16,000 |

^{*}Actual specifications may vary due to product enhancement. Please contact us for more details.

About us:

BSL Oilfield Services is a leading offshore equipment supplier, specializing in supply of quality offshore containers, baskets, CCUs, tanks, and equipment.